

Data sheet EPDM Siphon Roof Outlet (Perforated Flange)



Function:

Drain connector made from EPDM with special Siphon mechanism for circualr downpipe outlets, used to bond to EPDM sheet membranes and bituminous membranes around downpipe roof drainage outlets.

The special Siphon mechanism has a small well under the integrated leaf guard which fills then spills out over the sides to provide a U bend type air lock and seal to the downpipe below. This prevents foul odours emerging from the drainpipe.

The drain connector has a rough perforated flange to provide and over and under bond with either adhesive to the EPDM or within two layers of bituminous membrane.

The slightly conical shape of the spigot enables fast and simple installation into drainpipes. A series of rings along the outside of the spigot secures the outlet in place and prevents water rising from the inside of the drainpipe.

Always prime the outlet and membrane before installation.

Compatibility: They are compatible with EPDM sheet membranes, APP and SBS prefabricated

bituminous felts and liquid bituminous membranes.

Range: DN 50 - DN 63 - DN 75 - DN 90 - DN 110 - DN 125

Performance: Resistant to deterioration by the sun, ozone and other agents or chemicals normally found

in the atmosphere. They have excellent flexibility even at low temperatures. The

mechanical properties are maintained in the long term.

Operating temperature: -20°C; +70°C Included accessories: N/A


Recycled product: No Recyclable: Yes

Material: EPDM Optional accessories: Rigid extension shank

Flexible heating element

If not otherwise indicated, all measurements are expressed in millimetres.

Data sheet EPDM Siphon Roof Outlet (Perforated Flange)



Item	Description	Α	В	C	D	E	F	G
RO-EPDM-095-150-250-080-Z	EPDM "SIPHON" Roof Outlet (perforated flange) H250mm-D80mm	370	68	65	180	75	250	72
RO-EPDM-095-150-250-090-Z	EPDM "SIPHON" Roof Outlet (perforated flange) H250mm-D90mm	370	77	74	180	84	250	72
RO-EPDM-095-150-250-100-Z	EPDM "SIPHON" Roof Outlet (perforated flange) H250mm-D100mm	370	88	85	180	95	250	72
RO-EPDM-095-150-250-110-Z	EPDM "SIPHON" Roof Outlet (perforated flange) H250mm-D110mm	370	97	93	180	103	250	72

Additional Information:

For more information on interface with connectors etc. please refer to the corresponding Accessories datasheets.

