

Data sheet

TPE Extra Long Circular Roof Outlet (Perforated Flange)



Function: TPE circular downpipe outlets designed to be bonded to bituminous waterproofing

membranes around roof drainage downpipes.

They have a perforated flange to improve the watertight bond. The outlet is bonded in the sandwich method where it is bonded between two layers of waterproofing

membrane for and over-and-under seal.

The slightly conical shape of the spigot enables fast and simple installation into drainpipes. It has two rings on the spigot to prevent water travelling upwards from

the drainpipe.

Always prime the outlet and membrane before installation.

Compatibility: They are compatible with APP and SBS prefabricated bituminous felts and

bituminous coats.

Range: DN 80 - DN 90 - DN 100 - DN 110 - DN 125 - DN 140 - DN 150 - DN 160 - DN 200

Performance: Resistant to deterioration by the sun, ozone and other agents or chemicals normally

found in the atmosphere. They have excellent flexibility even at low temperatures.

The mechanical properties are maintained in the long term.

Operating temperature: -20°C; +70°C Included accessories: N/A

Recycled product: No Recyclable: Yes

Universal leaf excluders

Gravel excluders

Optional accessories:

Rigid extension shank

Flexible heating element


If not otherwise indicated, all measurements are expressed in millimetres.

Material:

TPE

Data sheet

TPE Extra Long Circular Roof Outlet (Perforated Flange)



Item	Description	Α	В	С	D	E	F
RO-TPE-030-160-600-080-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D80mm	370	65	63	72	70	600
RO-TPE-030-160-600-090-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D90mm	370	74	72	81	79	600
RO-TPE-030-160-600-100-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D100mm	370	85	83	92	90	600
RO-TPE-030-160-600-110-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D110mm	390	93	91	100	98	600
RO-TPE-030-160-600-125-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D125mm	390	107	105	114	112	600
RO-TPE-030-160-600-140-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D140mm	420	125	123	132	130	600
RO-TPE-030-160-600-150-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D150mm	420	135	133	142	140	600
RO-TPE-030-160-600-160-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D160mm	420	138	136	145	143	600
RO-TPE-030-160-600-200-Z	TPE Extra Long Circ.Outlet (perforated flange) H600mm-D200mm	460	178	176	185	183	600

Additional Information:

For more information on interface with connectors etc. please refer to the corresponding Accessories datasheets.

