

Data sheet

TPE Extension Shank



Function: TPE extension shanks are designed to be used with standard circular downpipe

outlets to extend the length of the 240mm long spigot to the desired length.

The end of the spigot on the outlet is slid into the top / mouth of the extension

shank.

The upper flaring at the top / mouth serves to accommodate silicone or other

sealant to help provide a secure, long term seal.

They have two rings towards the top of the shank which act as a gasket. They will grip the inside of the downpipe to secure the fit and prevent water rising up to the

top of the downpipe.

Compatibility: They can be used with all through wall / corner outlets supplied by Wallbarn.

Range: DN 40 - DN 60 - DN 75 - DN 80 - DN 90 - DN 100 - DN 110 - DN 125

DN 125 for HDPE pipe

Performance: Resistant to deterioration by the sun, ozone and other agents or chemicals normally

found in the atmosphere. They have excellent flexibility even at low temperatures.

The mechanical properties are maintained in the long term.

Operating temperature: -20°C; +70°C

Included accessories: N/A Optional accessories: N/A


Material: TPE

Recycled product: No Recyclable: Yes

If not otherwise indicated, all measurements are expressed in millimetres.

Data sheet

TPE Extension Shank



Item	Description	A	В	С	D	E
RO-TPE-210-040-240-040-Z	TPE Extension shank - 40mm	26	24	33	29	243
RO-TPE-210-040-240-060-Z	TPE Extension shank - 60mm	48	43	53	48	243
RO-TPE-210-040-240-075-Z	TPE Extension shank - 75mm	65	61	70	66	243
RO-TPE-210-040-240-080-Z	TPE Extension shank - 80mm	69	64	74	69	243
RO-TPE-210-040-240-090-Z	TPE Extension shank - 90mm	77	73	82	78	243
RO-TPE-210-040-240-100-Z	TPE Extension shank - 100mm	89	84	94	89	243
RO-TPE-210-040-240-110-Z	TPE Extension shank - 110mm	91	87	97	92	243
RO-TPE-210-040-240-125-Z	TPE Extension shank - 125mm	114	109	119	114	243
RO-TPE-210-041-240-125-Z	TPE Extension shank - 125mm – Special for HDPE Pipe	111	106	117	111	243

